



CORE HOLES:

	length	deviations, m	
		start	end
R-S146A	172.30	0.03	-0.24
R-S146B	163.60	0.04	-0.62
R-S146C	220.30	0.03	-1.25
R-S146E	45.10	0.00	-1.11
R-S146G	46.80	-0.30	+0.43
R-S146D	56.00	-0.30	+2.14
R-S146F	92.00	0.00	-2.11
R-S146H	81.80	0.00	0.00
R-S440-21	21.00	0.00	0.00
R-S440-23	20.00	0.00	0.00
R-S440-25	30.00	0.00	0.00
R-S144B	288.20	+5.00	+1.76

DRILL HOLE PARAMETERS:
 Analyses: cuau (%)
 Content classes (cuau below) 0.5000 1.0000 1.0000 - 2.5000
 Projection distance: front, m 5.00
 back, m 5.00
 Projection level: direction, gr 100.00
 slope, degree 90.00
 Projection: direction, gr 200.00
 slope, degree 0.00
 All the holes intersecting the projection level are drawn

DD SD S P OB RB EX GS CS

A/S Bidjovagge 1: 500
 Gruber 29.10.1991

X=-1460

X=-1460
 Y=750
 Z=-600

X=-1460
 Y=750
 Z=-350

X=-1460
 Y=1050
 Z= 600

X=-1460
 Y=1050
 Z=-350