

Technical drawing of a wall section. The drawing shows a cross-section of a wall with a base and a top surface. The base is divided into five segments with widths of 530, 870, 600, 770, and 330. The total width of the wall is 3500. The height of the wall is 1750. A vertical dimension of 240 is shown on the left side, indicating the height of a specific section. The drawing is labeled 'Fig. 10' in the bottom right corner.

Architectural drawing of a building facade with dimensions. The drawing shows a cross-section of a wall and roof structure. Key dimensions include:

- Overall width: 2000
- Overall height: 4480
- Roof slope: 1:12 (indicated by a triangle with a vertical side of 1 and a horizontal side of 12)
- Roof thickness: 250
- Roof overhang: 1750
- Wall thickness: 425
- Internal wall thickness: 1165
- Internal wall thickness: 585
- Internal wall thickness: 25
- Internal wall thickness: 25
- Internal wall thickness: 500
- Internal wall thickness: 1230
- Internal wall thickness: 1923.5
- Internal wall thickness: 800
- Internal wall thickness: 400
- Internal wall thickness: 1326.5
- Internal wall thickness: 300
- Internal wall thickness: 150
- Internal wall thickness: 1850

Technical drawing of a machine frame (Fig. 1) showing dimensions and components. The drawing includes the following details:

- Dimensions:**
 - Overall width: 3100
 - Overall height: 5050
 - Top flange width: 2700
 - Top flange thickness: 200
 - Internal width: 965
 - Internal height: 1500
 - Bottom flange thickness: 250
 - Vertical distance from top flange to first component: 350
 - Vertical distance between components: 700
 - Vertical distance from second component to third component: 900
 - Vertical distance from third component to motor coupling: 2850
 - Horizontal distance from left side to first component: 315
 - Horizontal distance between components: 1080
 - Horizontal distance from second component to centerline: 260
 - Horizontal distance from centerline to third component: 700
 - Horizontal distance from third component to right side: 280
 - Horizontal distance from left side to centerline: 1923.5
 - Horizontal distance from centerline to right side: 1100
- Components and Labels:**
 - Forankrbolter M30 x 1300 (Anchoring bolts)
 - Bremseklave (Brake lever)
 - Linstrammel (Line stamper)
 - Trommelaks. (Drum axle)
 - Forankrbolter M30 x 750 (Anchoring bolts)
 - Bremsetrom. (Brake drum)
 - Motoraksling (Motor coupling)
- Reference Lines:**
 - Line A (Horizontal, bottom)
 - Line B (Vertical, left)
 - Line C (Horizontal, middle)
 - Line E (Vertical, right)